

# COSPOLICH

## MODEL NUMBERS:

<b>UCF5-2M-ADS</b>	<b>UCF5-2M-SN MIL SPEC</b>
<b>UCF10-2M-ADS</b>	<b>UCF10-2M-SN MIL SPEC</b>
<b>UCF15-2M-ADS</b>	<b>UCF15-2M-SN MIL SPEC</b>
<b>UCF20-2M-ADS</b>	<b>UCF20-2M-SN MIL SPEC</b>
<b>UCF30-2M-ADS</b>	<b>UCF30-2M-SN MIL SPEC</b>

### APPLICATION

Designed for use in applications where horizontal or undercounter storage is required in place of the conventional vertical type.

### CABINET CONSTRUCTION

Exterior and interior of all standard cabinets, including front, sides, doors and louvered grill are constructed of heavy gauge, type 304 stainless steel.

Special attention was taken in engineering the doors of the Cospolich cabinet. A door unit was designed which could withstand the continuous use and abuse that is common in all food service applications.

Vinyl resilient gaskets which are preformed in frames, with welded corners, greatly inhibit bacterial growth and are easily replaceable.

Heaters, which are concealed under the thermal breaker strip around the door perimeter, prevent condensation.

### HARDWARE

Positive latches with magnetic back-up are included on all standard cabinets to assure positive latching and sealing. Incorporated into the latch is a replaceable keyed cylinder lock.

Heavy duty adjustable chrome plated hinges are provided on all standard cabinets. Also available, at no extra cost, are 180 degrees self-closing, cam-lift hinges with stay-open feature at 93 degrees.

Cabinet body and doors are insulated with foamed-in-place polyurethane foam, providing for excellent rigidity and the best insulating properties in the industry.

### REFRIGERATION SYSTEM

All components of the refrigeration system, with the exception of the evaporator, are bottom mounted on a heavy duty base frame behind a louvered grill which is easily removable without the use of tools. The condensing unit is mounted on a slide out rail for ease in cleaning and servicing.

All evaporator coils are copper tube. The refrigerant flow is monitored by an expansion valve for effective cooling.



### UCF20-2M-ADS (SN)

Temperature of the cabinet is factory adjusted, and the controls, along with the off/on switch are located in the condensing unit area.

Defrost cycles on specified low-temperature cabinets (ADS models) prevent the need for manual defrosting.

### SHELVING

Standard interior shelving consists of heavy-duty epoxy-coated steel wire with front rail. Each shelf is adjustable in one-inch increments. Stainless steel shelving and brackets are also available.

### U.L. and U.S.P.H.

This equipment is listed by Underwriters Laboratories, Inc. the National Sanitation Foundation and is built according to standards as set forth by the U.S. Public Health Service.

## THIS UNIT AVAILABLE IN OUR SPECIAL MODULAR CONSTRUCTION

### FEATURES

- Stainless steel interior and exterior (exposed)
- Oversized refrigeration system
- Anti-condensate door heaters
- Heavy-duty chrome-plated hardware
- Door with adjustable alignment
- Epoxy coated adjustable shelving with front rail
- Removable grill
- Polyurethane insulation
- Slide-out condensing unit
- Resilient gaskets
- Exterior dial thermometer
- Condensate Evaporator Pan
- Automatic activated interior lighting



SANITATION



CLASSIFIED TO NSF 7 - 1996

### OPTIONS

- Special dimensions
- Stainless steel adjustable shelving with front rail
- Mil specs units
- Heavy-duty adjustable legs
- Food files
- Spring closing hinges
- Aluminum construction for weight sensitive applications
- Fresh and sea water cooled condensing units
- Special voltage and currents

[www.cospolich.com](http://www.cospolich.com)

**2M**  
SERIES

Quality & Innovation Since 1937

# UNDERCOUNTER FREEZERS

MODEL NUMBERS:

UCF5-2M-ADS  
UCF10-2M-ADS  
UCF15-2M-ADS  
UCF20-2M-ADS  
UCF30-2M-ADS

UCF5-2M-SN  
UCF10-2M-SN  
UCF15-2M-SN  
UCF20-2M-SN  
UCF30-2M-SN

DATA	UCF5-2M-ADS (SN)	UCF10-2M-ADS (SN)	UCF15-2M-ADS (SN)	UCF20-2M-ADS (SN)	UCF30-2M-ADS (SN)
Capacity (lb / ltr)	6 / 170	8.5 / 514	13.3 / 377	18 / 510	27 / 765
Width (in / mm)	40 / 1016	49 / 1245	66 / 1676	84 / 2134	115 / 2921
Depth (in / mm)	27 / 686	27 / 686	27 / 686	27 / 686	28 / 711
Height (in / mm)	28 / 711	28 / 711	28 / 711	28 / 711	28 / 711
Weight (in / mm)	21.38 / 543	30.38 / 772	47.5 / 1207	65.5 / 1661	96.5 / 2451
Volume (in / mm)	22.5 / 572	22.5 / 572	22.5 / 572	22.5 / 572	22.5 / 572
Clearance (in / mm)	21.5 / 546	21.5 / 546	21.5 / 546	21.5 / 546	21.5 / 546
Door Height (in / mm)	25 / 635	25 / 635	25 / 635	25 / 635	26 / 660
Door Open 90° (in / mm)	50.38 / 1280	59.12 / 1503	50.12 / 1273	59.12 / 1503	57.75 / 1467
Door Width (in / mm)	21.38 / 543	30.12 / 767	21.12 / 536	30.12 / 767	27.5 / 705
Height (in / mm)	19.5 / 495	19.5 / 495	19.5 / 495	19.5 / 495	19.5 / 495
Number of Doors	1	1	2	2	3
Number of Shelves	1	1	2	2	3
Area (sq ft / sq m)	3.3 / .31	4.5 / .42	6.5 / .75	8.7 / 1	12.4 / 1
Price	234 / 105	260 / 117	380 / 171	460 / 207	544 / 245

DATA	UCF5-2M-ADS (SN)	UCF10-2M-ADS (SN)	UCF15-2M-ADS (SN)	UCF20-2M-ADS (SN)	UCF30-2M-ADS (SN)
Capacity (lb / ltr)	115	115	115	115	115
Width (in / mm)	5	6	7	7	8.8

TECHNICAL DATA	UCF5-2M-ADS (SN)	UCF10-2M-ADS (SN)	UCF15-2M-ADS (SN)	UCF20-2M-ADS (SN)	UCF30-2M-ADS (SN)
Door Type	1/4	1/4	1/4	1/4	1/3
Capacity (lb / HR)	1450 / 365	1955 / 493	1955 / 493	1955 / 493	2425 / 611


TECHNICAL DATA	UCF5-2M-ADS (SN)	UCF10-2M-ADS (SN)	UCF15-2M-ADS (SN)	UCF20-2M-ADS (SN)	UCF30-2M-ADS (SN)
Width (in / mm)	42 / 1067	51 / 1295	68 / 1727	86 / 2184	117 / 2972
Depth (in / mm)	30 / 762	30 / 762	30 / 762	30 / 762	31 / 787
Height (in / mm)	32 / 813	32 / 813	32 / 813	32 / 813	32 / 813
Weight (lbs / kg)	246 / 110	273 / 123	399 / 178	483 / 217	571 / 257
Volume (cu ft / ltr)	23 / 651	28 / 793	38 / 1076	48 / 1359	67 / 1898

[www.cospolich.com](http://www.cospolich.com)

MODEL SHOWN  
UCF20-2M-S (SN)



ELEVATION



HORIZONTAL SECTION



VERTICAL SECTION

# COSPOLICH

Naval Shipboard Models Available.

Post Office Box 1206 • Destrehan, Louisiana 70047  
Toll Free: 800-423-7761 • Local: 985-725-0222 • FAX: 985-725-0222