

COSPOLICH

MODEL NUMBERS:

UCR5-2M-S	UCR5-2M-SN MIL SPEC
UCR10-2M-S	UCR10-2M-SN MIL SPEC
UCR15-2M-S	UCR15-2M-SN MIL SPEC
UCR20-2M-S	UCR20-2M-SN MIL SPEC
UCR30-2M-S	UCR30-2M-SN MIL SPEC

APPLICATION

Designed for use in applications where horizontal or undercounter storage is required in place of the conventional vertical type.

CABINET CONSTRUCTION

Exterior and interior of all standard cabinets, including front, sides, doors and louvered grill are constructed of heavy gauge, type 304 stainless steel.

Special attention was taken in engineering the doors of the Cospolich cabinet. A door unit was designed which could withstand the continuous use and abuse that is common in all food service applications.

Vinyl resilient gaskets which are preformed in frames, with welded corners, greatly inhibit bacterial growth and are easily replaceable.

Heaters, which are concealed under the thermal breaker strip around the door perimeter, prevent condensation.

Interior lighting, a standard item in all refrigerator compartments, is activated by the door opening.

HARDWARE

Positive latches with magnetic back-up are included on all standard cabinets to assure positive latching and sealing. Incorporated into the latch is a replaceable keyed cylinder lock.

Heavy duty adjustable chrome plated hinges are provided on all standard cabinets. Also available, at no extra cost, are 180 degrees self-closing, cam-lift hinges with stay-open feature at 93 degrees.

Cabinet body and doors are insulated with foamed-in-place polyurethane foam, providing for excellent rigidity and the best insulating properties in the industry.

REFRIGERATION SYSTEM

All components of the refrigeration system, with the exception of the evaporator, are bottom mounted on a heavy duty base frame behind a louvered grill which is easily removable without the use of tools. The condensing unit is mounted on a slide out rail for ease in cleaning and servicing.



UCR20-2M-S (SN)

All evaporator coils are copper tube. The refrigerant flow is monitored by an expansion valve for effective cooling.

Temperature of the cabinet is factory adjusted, and the controls, along with the off/on switch are located in the condensing unit area.

SHELVING

Standard interior shelving consists of heavy-duty epoxy-coated steel wire with front rail. Each shelf is adjustable in one-inch increments. Stainless steel shelving and brackets are also available.

U.L. and U.S.P.H.

This equipment is listed by Underwriters Laboratories, Inc. the National Sanitation Foundation and is built according to standards as set forth by the U.S. Public Health Service.

THIS UNIT AVAILABLE IN OUR SPECIAL MODULAR CONSTRUCTION

FEATURES

- Stainless steel interior and exterior (exposed)
- Oversized refrigeration system
- Anti-condensate door heaters
- Heavy-duty chrome-plated hardware
- Door with adjustable alignment
- Epoxy coated adjustable shelving with front rail
- Removable grill
- Polyurethane insulation
- Slide-out condensing unit
- Resilient gaskets
- Exterior dial thermometer
- Condensate Evaporator Pan
- Automatic activated interior lighting



SANITATION



CLASSIFIED TO NSF 7-1986

OPTIONS

- Special dimensions
- Stainless steel adjustable shelving with front rail
- Mil specs units
- Heavy-duty adjustable legs
- Food files
- Spring closing hinges
- Aluminum construction for weight sensitive applications
- Fresh and sea water cooled condensing units
- Special voltage and currents

www.cospolich.com



Quality & Innovation Since 1937

UNDERCOUNTER REFRIGERATORS

MODEL NUMBERS:

UCR5-2M-S
UCR10-2M-S
UCR15-2M-S
UCR20-2M-S
UCR30-2M-S

UCR5-2M-SN MIL SPEC
UCR10-2M-SN MIL SPEC
UCR15-2M-SN MIL SPEC
UCR20-2M-SN MIL SPEC
UCR30-2M-SN MIL SPEC

DIMENSIONAL DATA

	UCR5-2M-S (SN)	UCR10-2M-S (SN)	UCR15-2M-S (SN)	UCR20-2M-S (SN)	UCR30-2M-S (SN)
Net Capacity (cu ft / ltr)	6 / 170	8.5 / 514	13.3 / 377	18 / 510	27 / 765
Width Overall (in / mm)	40 / 1016	49 / 1245	66 / 1676	84 / 2134	115 / 2921
Depth Overall (in / mm)	27 / 686	27 / 686	27 / 686	27 / 686	28 / 711
Height Overall (in / mm)	28 / 711	28 / 711	28 / 711	28 / 711	28 / 711
Interior Width (in / mm)	21.38 / 543	30.38 / 772	47.5 / 1207	65.5 / 1661	96.5 / 2451
Interior Depth (in / mm)	22.5 / 572	22.5 / 572	22.5 / 572	22.5 / 572	22.5 / 572
Interior Height (in / mm)	21.5 / 546	21.5 / 546	21.5 / 546	21.5 / 546	21.5 / 546
Depth Over Body (in / mm)	25 / 635	25 / 635	25 / 635	25 / 635	26 / 660
OA Depth with Door Open 90° (in / mm)	50.38 / 1280	59.12 / 1503	50.12 / 1273	59.12 / 1503	57.75 / 1467
Clear Door Width (in / mm)	21.38 / 543	30.12 / 767	21.12 / 536	30.12 / 767	27.5 / 705
Clear Full Door Height (in / mm)	19.5 / 495	19.5 / 495	19.5 / 495	19.5 / 495	19.5 / 495
Number of Doors	1	1	2	2	3
Number of Shelves	1	1	2	2	3
Shell Area (sq ft / sq m.)	3.3 / .31	4.5 / .42	6.5 / .75	8.7 / 1	12.4 / 1
Weight (lbs / kg)	234 / 105	260 / 117	380 / 171	460 / 207	544 / 245

ELECTRICAL DATA

Voltage	115	115	115	115	115
Total Amperes	5	6	7	7	8.8

REFRIGERATION DATA


Compressor H.P.	1/4	1/4	1/4	1/4	1/3
BTU / HR - KCAL / HR	1450 / 365	1955 / 493	1955 / 493	1955 / 493	2425 / 611

SHIPPING DATA


Width-Crated (in / mm)	42 / 1067	51 / 1295	68 / 1727	86 / 2184	117 / 2972
Depth-Crated (in / mm)	30 / 762	30 / 762	30 / 762	30 / 762	31 / 787
Height-Crated (in / mm)	32 / 813	32 / 813	32 / 813	32 / 813	32 / 813
Weight-Crated (lbs / kg)	246 / 110	273 / 123	399 / 178	483 / 217	571 / 257
Volume-Crated (cu ft / ltr)	23 / 651	28 / 793	38 / 1076	48 / 1359	67 / 1898

www.cospolich.com


MODEL SHOWN
UCR20-2M-S (SN)



ELEVATION



HORIZONTAL SECTION



VERTICAL SECTION

COSPOLICH

Naval Shipboard Models Available.

Post Office Box 1206 • Destrehan, Louisiana 70047
Toll Free: 800-423-7761 • Local: 985-725-0222 • FAX: 985-725-1564